

Investigation of Finemet nanocrystalline alloy coating obtained by the electric spark method

Kazan Federal University, 420008, Kremlevskaya 18, Kazan, Russia

Abstract

© Copyright 2018 Inderscience Enterprises Ltd. This paper discusses properties of the wear-resistant coating made of the 5BDSR nanocrystalline alloy obtained by the electric spark method (Finemet). It has been proved that an electric spark coating has a nanocrystalline structure which resembles the amorphous matrix with nanocrystals α -Fe. The coating thickness is 33 μm , its microhardness is 8461-11,357 MPa, and the wear resistance is $0.55 \times 10^4 \text{s/g}$. 5BDSR nanocrystalline alloy coating can be used to increase the wear resistance of machinery working surfaces.

<http://dx.doi.org/10.1504/IJNT.2018.094794>

Keywords

Electric spark treatment, Hardening, Microhardness, Multifunctional coating, Nanocrystalline alloy, Wear resistance

References

- [1] Kolomeychenko, A.V. and Kuznetsov, I.S. (2015) Teoriya i praktika elektroiskrovogo uprochneniya rezhushchikh detaley mashin amorfnyimi i nanokristallicheskimis splavami [Theory and practice of electric-hardening cutting machine parts amorphous and nanocrystalline alloys], Publishing house of Orel State Agrarian University, Orel (in Russian).
- [2] Ageev, E., Mizobata, K., Nakajima, T., Zen, H., Kii, T. and Ohgaki, H. (2015) 'Time-resolved detection of structural change in polyethylene films using mid-infrared laser pulses', Appl. Phys. Lett., Vol. 107, No. 4, p. 041904.
- [3] Ageeva, E.V., Khor'yakova, N.M. and Ageev, E.V. (2015) 'Morphology and composition of copper electrical spark powder suitable for sintering', Russ. Eng. Res., Vol. 35, No. 1, pp. 33-35.
- [4] Cadney, S. and Brochu, M. (2008) 'Formation of amorphous $\text{Zr}_{41.2}\text{Ti}_{13.8}\text{Ni}_{10}\text{Cu}_{12.5}\text{Be}_{22.5}$ coatings via the electrospark deposition process', Intermetallics, Vol. 16, No. 4, pp. 518-523.
- [5] Brochu, M., Heard, D.W., Milligan, J. and Cadney S. (2010) 'Bulk nanostructure and amorphous metallic components using the electrospark welding process', Assembly Automation, Vol. 30, No. 3, pp. 248-256.
- [6] Milligan, J., Heard, D.W. and Brochu, M. (2010) 'Formation of nanostructured weldments in the Al-Si system using electrospark welding', Appl. Surf. Sci., Vol. 256, No. 12, pp. 4009-4016.
- [7] Cadney, S., Goodall, G., Kim, G., Moran, A. and Brochu, M. (2009) 'The transformation of an Al-based crystalline electrode material to an amorphous deposit via the electrospark welding process', J. Alloys Compd., Vol. 476, Nos. 1-2, pp. 147-151.
- [8] Kolomeichenko, A.V., Kuznetsov, I.S. and Kravchenko, I.N. (2015) 'Investigation of the thickness and microhardness of electrospark coatings of amorphous and nanocrystalline alloys', Weld. Int., Vol. 29, No. 10, pp. 823-825.
- [9] Kolomeichenko, A.V. and Kuznetsov, I.S. (2014) 'Tribotechnical properties the electrospark coating of amorphous and nanocrystalline alloys based on iron', Friction and Wear, Vol. 35, No. 6, pp. 501-504.

- [10] Kolomeychenko, A.V., Kuznetsov, I.S., Rodichev, A.Y. and Penyashki, T.G. (2015) 'K voprosu polucheniya v elektroiskrovykh pokrytiyakh amorfnykh i nanokristallicheskiykh struktur [On the question of getting in electric-spark coatings of amorphous and nanocrystalline structures]', Remont. Vosstanovlenie. Modernizatsiya [Repair. Recovery. Modernization], No. 5, pp. 33-36 (in Russian).
- [11] Adigamov, N.R., Sharifullin, S.N. and Podgaraya, K.S. (2013) 'Vysokoeffektivnye tekhnologii po modernizatsii toplivnykh nasosov vysokogo davleniya avtotraktornykh dizel'nykh dvigateley [Efficient technology for the modernization of the high-pressure fuel pumps, automotive diesel engines]', Trudy GOSNITI [Proceedings GOSNITI], Vol. 113, pp. 206-214 (in Russian).
- [12] Adigamov, R.N., Lyalyakin, V.P., Soloviev, R.Y. and Sharifullin, S.N. (2016) 'Plazmennye tekhnologii v povyshenii effektivnosti raboty toplivnykh nasosov vysokogo davleniya dizel'nykh dvigateley [Plasma technology in improving the efficiency of the diesel engine high pressure fuel pumps]', Svarochnoe proizvodstvo [Welding Engineering], No. 2, pp. 49-51 (in Russian).